

Technical Data Maskin Mekano STE 2-24

| | |
|--------------------------|---|
| Manufacturer | Maskin Mekano |
| Model | STE 2-24, 2 decks |
| Type | Single axle four-bearing |
| Stroke | 12 mm |
| Inclination | 11° |
| Screening area | 2,0x1,2 m per deck |
| Screenbox | Huckbolted, reinforced by welding |
| Screen tensioning | Upper deck side tensioned Lower deck end tensioned |
| Motor | Electric motor 5,5 kW, 380 V |
| Operation | approx. 800 rpm |

Technical Data Maskin Mekano STE 2-53

| | |
|--------------------------|---|
| Manufacturer | Maskin Mekano |
| Model | STE 2-53, 3 decks |
| Type | Single axle four-bearing |
| Stroke | 12 mm |
| Inclination | 11° |
| Screening area | 4,4x1,2 m per deck |
| Screenbox | Huckbolted, reinforced by welding |
| Screen tensioning | Upper deck side tensioned (three units at 1.5 m) Lower deck end tensioned (two units at 2.2 m) |
| Motor | Electric motor 11 kW, 380 V |
| Operation | approx. 800 rpm |

Technical Data Maskin Mekano STE 3-78

| | |
|--------------------------|---|
| Manufacturer | Maskin Mekano |
| Model | STE 3-78 |
| Type | Single axle four-bearing |
| Stroke | 12 mm |
| Inclination | 11° |
| Screening area | 4,8x1,6 m per three decks Upperdeck incl. prescreening surface 5,6x1,6 |
| Screenbox | Huckbolted, reinforced by welding |
| Screen tensioning | All units sidetensioned |
| Motor | Electric motor 16 kW, 380 V |
| Operation | approx. 800 rpm |