

Technical Specification Maskin Mekano Ls 902

<i>Transport Length</i>	16,0 m
<i>Transport Width</i>	3,0 m
<i>Transport Height</i>	4,0 m
<i>Machine Weight</i>	approx. 16,7 tonnes (not including Dieselgenerator set)
<i>Boggie pressure</i>	approx. 12,3 tonnes
<i>Screenbox</i>	STE 2-53. Screening surface 1.2x4.4 m on two decks Single axle mechanically controlled with 12 mm stroke 11° incline Electric motor 11.0 kW, 400 V
<i>Beltfeeder</i>	Belt width 800 mm Length 11.0 m Electric motor 7.5 kW, 400 V (Variable speed)
<i>Reject grid</i>	Standard distance between bars 180 mm, adjustable Hydraulic tipping, self cleaning
<i>Side conveyors</i>	Belt width 650 mm Length 7.6 m Electric drum motor 3.0 kW
<i>Rear conveyor</i>	Belt width 1200 mm Length 8.3 m Electric drum motor 4.0 kW
<i>Electric equipment</i>	Distribution box with safety breaker, safety disconnection breaker, emergency stop, preregulator as well as extra motor socket. Power inlet with 125 A CEE-device
<i>Hydraulic equipment</i>	Hydraulic aggregate for setting up, folding of the conveyors in and out and grid lift. Motor 4,0 kW
<i>Wheel- and towing device</i>	Bogie with brakes and plate spring. Wheel dimension 22,5/65/385, 10 bolt. Towing device, 2" kingping.